

Baltic

Technical Specifications

Manufacturing method	: Level loop
Pile type	: Looppile
Pile fibre	: 100% PA6 SD
Gauge	: 1/10"
Pile weight	: 550 gr/m ²
Pile height	: 3.0 mm
Total weight	: 1.510 gr/m ²
Total thickness	: 4.5 mm
Tuft density	: 177.750/m ²
Tile size	: 400 cm
Backing	: Actionback



Discover more!

Performance

Use classification	EN 1307	: 33
Caster chair test	EN 985	: A, Intensive use
Abrasion	EN 1963	: Pass
Vettermann test	EN 9405	: Pass
Dimensional stability	EN 986	: Pass
Thermal isolation	ISO 8302	: 0.06 m ² K/W
Sound absorption	ISO 140-8	: 20 dB
Luxury class	EN 1307	: LC2
DOP-nr		: 1016-2612
Prodis-nr		: C82D284D

Electrostatic

Static loading		: Anti-static
Walking test	EN 1815	: ≤ 0.3 KV
Horizontal resistance	ISO 1096 5	: 5 x 10.10 Ohm
Vertical resistance	ISO 1096 5	: 5 x 10.10 Ohm

Flammability

Reaction to fire EN ISO 13501-1	: Cfl-s1
Reaction to fire BS 4790	: Low radius of effect of ignition

Acoustics


Sound absorption EN ISO 10140	: 0.15
Impact sound insulation EN ISO 354	: 24 dB

Colour fastness

Light	ISO 105 B02	: 7.0 – 8.0
Rubbing	ISO 105 x12	: 4.5
Water	ISO 105 E01	: 5.0

Maintenance

Regular vacuum cleaning is essential. Spills and surface stains can be removed by sponging with a damp cloth, or for more resistant stains, with a mild detergent solution.



Betap has the right to alter each product specification in order to improve the carpet according to the newest technological applications.

